

**TECHNICAL DATA SHEET**

**4 inch Wing Nut High Pressure (15,000 PSI)  
 Turbine Flowmeters for Liquid Service**

(for water, Liquid Carbon Dioxide and Cement Slurry\*)



Hoffer now has available a 4" WECO 1502 turbine flow meter (15 KSI MAWP) with the full flow capacity of a conventional 4" flow meter. Other 4" WECO 1502 turbine meter designs have been limited in flow range to a few hundred GPM. The Hoffer design has a flow capacity of 75 to 1250 GPM standard and 50 to 1500 GPM over an extended range.

Made from high strength A-286 austenitic stainless steel, the meter body is rated to a full 15,000 PSIG for conventional service and 10,000 PSIG for sour service. The new size is an extension to the very successful Hoffer Wing Nut Meter Series (1" to 3" sizes) used extensively in oil and gas well servicing and reflects Hoffer's commitment to meeting new customer needs.

Model Number								Technical Data				
Flowmeter Size (Inches)				(Ref. Note 1) Linear Flow Range (US GPM)	(Ref. Note 2) Bearing Types	(Refer Note 3 for more options) Standard Magnetic Pickup Coil	Wing Nut End Fitting - Savage (-S) or FMC (-F) Nuts and Segments	Service Types	Nominal Pulses/Gallon 'K' Factor	Nominal Max. Freq. (Hz)	Length (inches)	
Wing Nut Size (Inches)												Min.
Model HO	4	X	4	-75 -50	-1250 -1500	-BP or -T	-1MX	-1502-S -1502-F	-H2O -CO2 -CS	20.75	435 520	12

**FLOW RANGE (Note 1)** Ranges are standard ranges — other ranges are available. Contact Hoffer Flow Controls Engineering.

**BEARING TYPE (Note 2)**  
 (–BP) Hybrid ceramic for 1", self-lubricating shielded ball bearings can be used on CO2 and H2O and never on Cement/Sand Slurry.  
 (–CB) Hybrid ceramic, self-lubricating shielded ball bearings can be used on CO2 and H2O and never on Cement/Sand Slurry.  
 (–T) Tungsten Carbide sleeve bearings can be used on H2O and CS and never on Liquid CO2.

**PICKUP COILS (Note 3)**  
 (–1MX) One magnetic pickup coil.  
**Optional** (–2MX180) Two magnetic pickup coils @ 180°.  
 (–1ISM)X Intrinsically Safe magnetic coil.  
 (–2ISM)X Two Intrinsically Safe magnetic coils.  
 (–1ISM-ATEX) One ISM ATEX coil.  
 (–2ISM-ATEX) Two ISM ATEX coils.  
 (–RPM\_\_ )X Redi-Pulse magnetic pickup coil providing a user specified conditioned pulse output. See Redi-Pulse Technical Data Sheet for available options.  
 (–DMX\_\_ )X Intrinsically Safe Redi-Pulse magnetic pickup coil. See Intrinsically Safe Redi-Pulse Technical Data Sheet for available options.

**RISER & EXPLOSION-PROOF COIL ENCLOSURES** (–E2) 1" MNPT riser with E2 coil enclosure. (See chart)\*\*

**SPECIAL FEATURES (add at end of Model No.)**  
 (–CE) CE mark required for Europe.  
 (–SP) Special features that are not covered in the Model number, use –SP and a written description.

**E2 EXPLOSION-PROOF/FLAME-PROOF ENCLOSURE WITH 3/4" FNPT MOUNT AND 3/4" CABLE ENTRY RATINGS:	
FM:	CLASS I, DIV. 1, GR. ABCD, CLASS II/III, DIV. 1, GR. EFG, TYPE 4X
CSA:	CLASS I, DIV. 1, GR. ABCD, CLASS II, DIV. 1, GR. EFG, CLASS III, TYPE 4X EX D IIC, CLASS I, ZONE 1, IP 66
ATEX:	EX II 2GD Ex d tD IIC, IP66/68
IEC:	EX D IIC IP68

FLOWMETERS ARE SUPPLIED WITH A 10-POINT CALIBRATION AND WITH 'K' FACTOR TAG ATTACHED TO METER.

\*FLOWMETER LIFE IS LIMITED IN CEMENT/SAND SLURRY. CUSTOMER MUST SPECIFY MAXIMUM PARTICULATE SIZE ON CEMENT/SAND SLURRY APPLICATIONS.

# GENERAL SPECIFICATIONS:

- Linearity:**  $\pm 0.5\%$  of reading ( $\pm 0.25\%$  typical) over tabulated linear flow range.
- Repeatability:**  $\pm 0.1\%$  over tabulated useable range.
- Temperature Range:**  $-450^{\circ}$  to  $+450^{\circ}$ F (Standard).
- Pressure Drop Characteristics:** Request graphical data.
- Overrange:** 150% of maximum flow (intermittently).
- Construction:** Housing - High strength A-286 austenitic stainless steel  
Internals - All stainless steel (except "T" bearings).

<b>4" Wing Nut Calibrated Spare Internal Kits</b>						
Flowmeter Size (Inches)		(Ref. Note 1) Linear Flow Range (US GPM)		(Ref. Note 2) Bearing Type		Service Types
		Min.	Max.			
Part Number Kit (Note 4)	HO4	-75 -50	-1250 -1500	-BP -T	-internals-W	-H2O -CO2 -CS
<b>Note:</b> Internal Kits and rotors are calibrated and supplied with 'K' factor.						

**Note 4:** Kit 1 internals for Model HO 2 X 1.

**Note 5:** Retainer Ring RR181 supplied with 2" kit.

**Note 6:** Retainer Ring RR262 supplied with 3" kit.

Hoffer also offers Wing Nut flowmeters in sizes 1" through 3" for both liquid and gas applications. Please see our Wing Nut High Pressure Turbine Flowmeters for Liquid Service Technical Data Sheet HO-WF-XXX and our Wing Nut High Pressure Flowmeters for Gas Service HO-WG-XXX.



**H HOFFER FLOW CONTROLS, INC.**  
 107 Kitty Hawk Lane, P. O. Box 2145, Elizabeth City, NC 27906-2145  
 800-628-4584    252-331-1997    FAX 252-331-2886  
[www.hofferflow.com](http://www.hofferflow.com)    email: [info@hofferflow.com](mailto:info@hofferflow.com)

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specification are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

The quality system covering the design, manufacture and testing of our products is certified to International Standard ISO 9001.

