

# TURBINE FLOWMETERS BY **HOFFER**

Perfecting Measurement™

# HIT-4L

## Temperature & Pressure

## Flow Computer for LIQUIDS

### Product Bulletin Hit-4L-120A

# TECHNICAL DATA SHEET

The **HIT-4L** is a **compact Digital Flow Computer for Liquids** with temperature, pressure, and viscosity compensation. The HIT-4L is configurable from the instrument front panel keypad or via Modbus communications.

## OUTSTANDING FEATURES

- ◆ **Temperature, Pressure, and Viscosity Compensation**
- ◆ **LCD display for Total, Rate, Temperature and Pressure**
- ◆ **Up to 20-point Linearization**
- ◆ **CSA/ATEX/IECEX hazardous location certifications available**
- ◆ Internal battery backup
- ◆ Data Logging: Hourly Total, Daily Total, Event Logs
- ◆ Non-resettable Grand Total
- ◆ Full front panel operation with magnetic pointer through enclosure
- ◆ 4-20mA analog output proportional to flow rate
- ◆ Optional Scaled Pulse or Raw Pulse Output representing an incremental total volume
- ◆ Alarm Output with dual set point configurable for Rate or Total
- ◆ Magnetically operated switch for Total reset
- ◆ Configuration and Totals stored in non-volatile memory. Totals saved when pressing ► button.
- ◆ Modbus Communications Protocol via RS485
- ◆ Real Time Clock

## SPECIFICATIONS

### DISPLAY:

LCD, updated every 1 second

### TOTAL:

8 digits 3/8" high. Resettable using a magnet, a contact closure, front panel keypad or via Modbus communications.

### TOTAL UNITS:

GAL, LIT, FT3, M3, BBL, KG, LB

### GRAND TOTAL, TEMPERATURE, PRESSURE:

8 digits 3/8" high

Display by pressing the ▲ button.

### RATE:

6 digits 1/2" high

### RATE UNITS:

/SEC, /MIN, /HR, /DAY



Turbine flow meter sold separately

### K-FACTOR:

The pulses per unit of Total (e.g. pulses/GAL) are configurable in the range 0.001 to 9,999,999

### LINEARIZATION:

2-20 points

### DECIMAL POINTS:

Decimal point positions are configurable for 0, 0.0, 0.00, or 0.000 for rate, total and K-factor.

### ACCURACY:

Total and Rate: +/-0.01% of reading,  
+/- 1 count

### MAGNETIC PICKUP INPUT:

Frequency Range: 0.2 Hz to 5000 Hz  
Signal Level: 30mV<sub>p-p</sub> to 30 V<sub>p-p</sub>

### MCP/RF PICKUP INPUT

#### PULSE INPUT:

Opto-Isolated

Frequency Range: 2 Hz to 3000 Hz

Internal pull-up 10KΩ to +DC

Signal Level: 0 to +DC

Low (Logic 0): <1 VDC

Min Pulse width: 0.1 msec

#### CONTACT CLOSURE INPUT:

Frequency Range: 0 Hz to 5000 Hz

Internal Pull-up: 220 kΩ to +3.3 VDC

#### RESET:

Signal Type: Contact closure

Min Time On: 25 msec

Internal Pull-up: 35 kΩ to +3.3 VDC

External Magnet: Activates internal switch

#### ANALOG OUTPUT:

Type: 4-20 mA follows rate

Accuracy: 0.02% Full Scale @ 20°C

Temperature Drift: 40 ppm/°C

#### DENSITY/VISCOSITY COMPENSATION:

2-20 points table

## HIT-4L ORDERING INFORMATION

### TEMPERATURE INPUT:

Type: \*4-20 mA, 100Ω RTD  
DIN385

### PRESSURE INPUT:

Type: \*4-20 mA  
\*4-20 inputs not available with  
battery or loop power.

### PULSE OUTPUT:

Type: 0-5V TTL, Open Collector (30  
VDC, 100 mA max)  
Divider: 0.01, 0.1, 1, 10, 100  
Pulse Width: Adjustable 4ms  
to 300ms  
Max Frequency: 100 Hz

### ALARM OUT WITH DUAL SET POINT:

Type: 0-5V TTL, Open Collector (30  
VDC, 100 mA)  
Function: Rate or Total

### DC POWER/LOOP POWERED:

Voltage: 8 to 30 VDC  
Current: <24 mA  
Loop Burden: 8 VDC  
Supply Backup: C-size 3.6V Lithium  
battery or battery pack for Ex d certified  
system.  
Protection: Reverse polarity, overvoltage

### BATTERY POWERED:

Two (2) C-size 3.6V Lithium batteries  
Battery Life: 2 years typical  
Ex System - battery pack (4xAA)  
Battery Life: 1 year typical

### SERIAL PORT RS485:

Protocol: Modbus RTU  
Function: Data Logging, Configuration,  
Process Monitor

### PHYSICAL:

Op. Temperature:  
-40°F(-40°C) to 176°F (80°C)  
Humidity:  
0-90% Non-Condensing  
Enclosure: NEMA, Aluminum  
(Approx. 5"x5"x5", 3 Lbs.)

Data Logging	
Hourly Total Log:	768
Daily Total Log:	378
Event Log:	345
<b>Accessing Logs:</b>	
Via Modbus communication Up to 100 latest flow logs are viewable on the front panel	

**HIT-4L- A -B- C -D -E -F -G -H -I**

**A. Enclosure Style**

(2) NEMA 4X  
(3\*) Aluminum Casting Powder Coated  
Enclosure (IP66)  
(7\*) Stainless steel enclosure (IP66)  
(P) Panel mount  
(PD) Panel mount w/door and lock (IP40)  
(PF) Panel mount w/clear flexible PVC  
cover (IP65 front only)  
**\*Options for 3 and 7**  
(\_M) M20 thread  
(\_S) Sunshade

**B. Input Power**

(B) Battery Powered  
(L) 4-20 MA Loop Power  
(D) 12 to 30 VDC External Power  
(AC\_) Universal 100-240vac @  
0.15A 50/60 HZ

**C. Pulse Input**

(M) Magnetic Coil  
(R) Isolated pulse, RP, Hall  
(RF) Modulated Carrier Coil

**D. Pulse Output**

(5) 0-5V TTL/CMOS  
(OC) Open Collector

**E. Alarm**

(5) 0-5V TTL/CMOS  
(OC) Open Collector

**I. Special Features**

(CE) CE mark required  
for Europe (pending)  
(X) None

**H. Communication Port**

(T) Internal terminal block  
(U) External USB for Nema 4X  
(X) None

**G. Mounting**

(X) Remote Mounting  
(FX) Style 3 or 7 enclosure mounted on  
turbine  
(FXHT) Style 3 or 7 enclosure w/8"  
riser mounted on turbine  
(F) NEMA 4X mounted on turbine  
(FHT) NEMA 4X w/8" riser mounted  
on turbine  
(NP) NEMA 4X enclosure pipe  
mounting kit 2" pipe & smaller

**Certified Mounting Options for  
Style 3 and 7 Enclosures:**  
(MX\_) Meter mounted. Process temp  
-40°C to +78°C.  
(MA\_) Meter Mounted w/ ATEX riser.  
Process temp -40°C to +78°C.  
(RX\_) Remote mounted. Includes E2  
junction box and 1"x3/4" SS adapter.  
(RA\_) Remote mounted w/ ATEX riser.  
Includes E2 junction box.

**Union Options:**  
(\_U1) 1" Ex-proof union for MX or RX  
(\_U2) 3/4" Ex-proof union for MA or RA

**F. Compensation Method**

(X) No Compensation  
(TP1\_) Temperature and pressure  
transmitter inputs (4-20mA)  
(TP2\_) 100 OHM RTD/Pressure  
transmitter (4-20mA)  
(UVC) Universal Viscosity Curve

### Enclosure Ex d Ratings: Certified Systems for Style 3 & 7

**CSA/FM:** CLASS I, DIV.1, GR. C,D; CLASS II, DIV.1, GR. E,F,G; CLASS III, T6; Type 4X;  
CLASS I ZONE 1 AEx db IIB, T6 Gb IP66  
ZONE 21 AEx tb IIIC T80°C Db IP66  
Ex db IIB T6 Gb; Ex tb IIIC T80°C Db; IP66

**ATEX/IECEx:**  
II 2 G Ex db IIB T6 Gb; IP66  
II 2 D Ex tb IIIC T80°C Db; IP66

H

HOFFER FLOW CONTROLS, INC.

107 Kitty Hawk Lane, P. O. Box 2145, Elizabeth City, NC 27906-2145  
800-628-4584 252-331-1997 FAX 252-331-2886  
www.hofferflow.com email: info@hofferflow.com

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.



The quality system covering the design, manufacture and testing of our products is certified to International Standard ISO 9001.

